



Panel C4

Scene controller, 4-inch display · \$299



SPECIFICATIONS

Function	Scene controller, no local load switching
Display	4 inch, 720 x 720, 60 Hz
Scenes	8 on screen, unlimited stored
Thread role	Border router
Energy view	Whole-home aggregate
Neutral required	Yes
Proximity wake	Yes, dims to black at night
Weight	214 g
Housing	UL 94 V-0 polycarbonate, tempered glass front
Supply	100 to 240 V AC, 50/60 Hz
Radio	802.15.4 Thread, Bluetooth LE for commissioning
Protocol	Matter 1.3
Module depth	39 mm
Faceplate	88 x 88 mm (EU/UK/AU) or 70 x 115 mm (US)
Operating temp	-5 to 40 C

IN THE BOX

Controller module, faceplate, mounting screws, quick-start card

COMPLIANCE

Standards	UL 20 (US/CA), EN 60669 (EU/UK), AS/NZS 3112 (AU/NZ)
Certification	Matter 1.3 certified, Thread Group member
Declaration of Conformity	SW-DoC-C4-2026
Warranty	2 years, extendable to 5

Issued 2026. Figures are typical at 230 V unless stated. Installation must comply with local wiring regulations and, in most regions, be carried out by a qualified electrician.